

PRODUCT SPECIFICATIONS

# 2x4 Flatlight™ Luminaire

Surface mountable or for T-grid bar ceilings





**ADVANTAGES**

- Internal driver for slim form factor
- Edge-lit LED for superior white and brightness uniformity
- 90° bezel edge
- Lasts 60%\* longer than standard troffer lighting
- 2 gang switch compatible for 100% / 50% on lumen output
- Low heat dissipation - reduce HVAC costs
- Low energy consumption
- Directly replaces fluorescent fixture and tube
- Environmentally positive - RoHS compliant
- Type IC Rated
- DLC certified for high energy efficiency for surface mount or into T-grid bar
- Durable diffuser for easy cleaning
- 5 year limited warranty

**APPLICATIONS**

Suitable for dry and damp locations



**SPECIFICATIONS**

Model Number	MLT24C40MDUP
Power	48 W
AC Voltage, Frequency	120~277V, 50/60 Hz
Color Temp (nom.)	4000K
Operation Temp	- 20°C ~ 40°C
CRI	84
Lumen Output (nom.)	4800 lm
Efficacy	100 lm/W
Lighting mode (pwr in/out)	2-switch wiring 100% / 50%
Lifetime Rating	60,000 Hrs
Finish/Material	White architectural grade aluminum

**PACKAGING**

Weight	21.4 lbs.
Mounting plate weight	5.4 lbs.
Size (L x W x H) (±0.1 in)	47.78 x 23.78 x 0.88 in
Box Dimensions	51.77 x 27.56 x 2.6 in
Gross Weight	33.2 lbs
UPC	8 5730200504 8



Contact Information 888-925-7494 · [www.pixilighting.com](http://www.pixilighting.com)

\*Based on standard ballast average lifetime

